

VINYL SPECIFICATIONS

Vinyl Size should be **EQUAL** to Frame Size. Be sure vinyl media has **RAW EDGE**. No Hems, Grommets, or Beading of any kind. Vinyl media should be **ROLLED on a tube**, rather than folded and boxed, whenever possible.

Vinyl Size should be **EQUAL** to Frame Size. The Frame has a "Cover Plate" which hides the outer 3" of the vinyl media.



← **TRIM SIZE: Size of Printed Vinyl, edge-to-edge.** →

SAFE ZONE: 6" Inside of TRIM Size, to allow for safe clearance and optimal appearance of key images and text.



ACCEPTABLE FILES

JPEG, PDF, TIFF

All layers must be flattened.

Maximum File Size: 120MB

CMYK Files are preferred. All RGB Files will be converted to CMYK, which will result in color shifts, and may lead to undesirable results.

Recommended Min. DPI: 100
(@ 100% of Actual Finished Size)
Min. DPI @ ½ Scale: 200

Please build files to the bleed, keeping all important visual elements inside the safe zone.

EXAMPLE:

Frame Size (Outer Dim): 180"w x 96"h
Vinyl Size or "Trim Size": 180"w x 96"h
Bleed Size: 180"w x 96"h
Viewable Opening (V.O.): 174"w x 90"h
"Safe Zone" / "Live" Area: 168"w x 84"h

Ackland has created an Easy-to-Use Framework for Sign Pros to Produce Spectacular Advertising Graphics on Buildings, Walls & Trucks, to Boost Profits and Increase Repeat Sales. Thank You for Your Business!

1-866-928-9744